





Product Type: High Current Branch Terminal

Product Name: SPDB16x3-4x6

Product Description: Connection method: Screw connection, IEC Rated Current: 80A, IEC Rated Voltage: 690V, Number of connections: 7, Number of levels: 1

Product Size



Parameters

 SUPU ID	SPDB16x3-4x6
 Width	38.4mm
 Number of connections	7
 Connection method	Screw connection

☞ Protection Level	IP20
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Ambient temperature (operation)	-40℃~105℃
☞ Ambient temperature (assembly)	-5℃~70℃
☞ Ambient temperature (storage)	-25℃~60℃
☞ Permissible humidity (storage/transport)	30%~70%

Technical data

☞ IEC Rated Current	80A
☞ IEC Rated Voltage	690V
☞ Degree of pollution	3
☞ Rated impulse voltage	2.5KV
☞ Locking screw Specification	M4/M5
☞ Locking screw torque	1.2N·m/2.4N·m
☞ Stripping length	13-14mm/10-11mm
☞ Connection capacity AWG	2.5-16mm ² /2.5-6mm ²
☞ 短路电流（峰值）	/
☞ 短路电流>1S	/

Commercial data

☞ Order No	SPDB3x16-4x6
------------	--------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-12 11:03

The right to modify data belongs to SUPU.