




Product Type: Din rail power supply

Product Name:SDP2-1AC24-120

Product Description: Single phase full range, 24V/120W, DC OK remote monitoring, DIN 35 rail mounting

## Product Size



## Parameters

⌘ SUPU ID	SDP2-1AC24-120
⌘ Protection Level	IP20
⌘ Operating temperature range	-40~+70°C
⌘ Terminal block	MC-TC5.0H2P-BK MC-TC5.0H3P-BK-0001-RZ MC-TC5.0H4P-BK-0001
⌘ DC OK	Yes
⌘ Dimensions(mm)	127 * 115* 35

## Technical data

☞ IEC Rated Current	2.2A
☞ IEC Rated Voltage	AC:264V DC:370V
☞ Nominal input	AC、DC
☞ Efficiency	88%
☞ Ripple noise	150mVp-p
☞ Input frequency	63HZ
☞ Peak load capacity	150%
☞ Withstand voltage	I/P-O/P : 3000Vac.60S,≤10mA I/P- PE : 1500Vac.60S,≤10mA O/P- PE : 700VDC.60S,≤10mA
☞ Working altitude	≤3000m

## Commercial data

☞ Order No	SDP2-1AC24-120
☞ Packing unit	PCS
☞ Minimum order quantity	1
☞ Single piece weight	0.51KG

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2026-04-25 20:07

The right to modify data belongs to SUPU.