





Product Type: Screw terminal

## Product Name: TU6-2-GY

Product Description: Connection method: Screw connection, IEC Rated current: 41A, IEC Rated Voltage: 1000V, Number of connections: 2, Number of levels : 1, Rated cross section: 26-8AWG

### Product Size



### Parameters

|                                                                                                         |          |
|---------------------------------------------------------------------------------------------------------|----------|
|  SUPU ID               | TU6-2-GY |
|  Width                 | 8.2mm    |
|  Number of levels      | 1        |
|  Number of connections | 2        |

|                                            |                              |
|--------------------------------------------|------------------------------|
| ☞ Connection method                        | Screw connection             |
| ☞ Protection Level                         | IP20                         |
| ☞ Insulation material                      | PA66                         |
| ☞ Insulation material group                | I                            |
| ☞ Contact material                         | Copper alloy                 |
| ☞ Contact plating                          | Sn,Plated                    |
| ☞ Ambient temperature (operation)          | -40°C~105°C                  |
| ☞ Ambient temperature (assembly)           | -5°C~70°C                    |
| ☞ Ambient temperature (storage)            | -25°C~60°C                   |
| ☞ Permissible humidity (storage/transport) | 30%~70%                      |
| ☞ Product type                             | Terminal block of side-entry |

## Technical data

|                                                 |                       |
|-------------------------------------------------|-----------------------|
| ☞ IEC Rated Current                             | 41A                   |
| ☞ IEC Rated Voltage                             | 1000V                 |
| ☞ Overvoltage category                          | III                   |
| ☞ Degree of pollution                           | 3                     |
| ☞ Rated impulse voltage                         | 8kV                   |
| ☞ UL Rated Current                              | 50A                   |
| ☞ UL Rated Voltage                              | 600V                  |
| ☞ Conductor cross section rigid                 | 0.2-10mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2-6mm <sup>2</sup>  |
| ☞ Conductor cross section flexible,with furrule | 0.2-6mm <sup>2</sup>  |
| ☞ Locking screw Specification                   | M4                    |

|                             |         |
|-----------------------------|---------|
| ⌘ Locking screw torque      | 1.2N.m  |
| ⌘ Fixed Screw Specification | /       |
| ⌘ 固定螺钉扭矩                    | /       |
| ⌘ Stripping length          | 10mm    |
| ⌘ Use group                 | B/C     |
| ⌘ Rated cross section       | 26-8AWG |
| ⌘ UL Rated Current          | 50A     |
| ⌘ UL Rated Current          | 600V    |

## Commercial data

|            |          |
|------------|----------|
| ⌘ Order No | TU6-2-GY |
|------------|----------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



---

Date:2026-03-12 13:08

The right to modify data belongs to SUPU.