





Product Type: Plug-in terminal-Plug

Product Name:MC-  
RU3.81SH04-0001

Product Description: Pitch:3.81mm Rated  
Voltage : 160V Rated Current:8A  
colour : customizable

## Product Size



## Parameters

|                         |                    |
|-------------------------|--------------------|
| ☞ SUPU ID               | MC-RU3.81SH04-0001 |
| ☞ Pitch                 | 3.81               |
| ☞ Number of levels      | single layer       |
| ☞ Number of connections | 4                  |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | -                                |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

Technical data

|                                                 |                 |
|-------------------------------------------------|-----------------|
| ☞ IEC Rated Current                             | 8A              |
| ☞ IEC Rated Voltage                             | 160V            |
| ☞ Overvoltage category                          | III/III/ II     |
| ☞ Degree of pollution                           | 3 2 2           |
| ☞ Rated impulse voltage                         | 2.5KV2.5KV2.5KV |
| ☞ UL Rated Current                              | 8A - 8A         |
| ☞ UL Rated Voltage                              | 300V - 300V     |
| ☞ Conductor cross section rigid                 | -               |
| ☞ Conductor cross section flexible              | -               |
| ☞ Conductor cross section flexible,with furrule | -               |
| ☞ Locking screw Specification                   | -               |
| ☞ Locking screw torque                          | -               |
| ☞ Fixed Screw Specification                     | -               |
| ☞ 固定螺钉扭矩                                        | -               |

|                       |       |
|-----------------------|-------|
| ☞ Stripping length    | -     |
| ☞ Use group           | B/C/D |
| ☞ Rated cross section | -     |

|                 |                    |
|-----------------|--------------------|
| Commercial data |                    |
| ☞ Order No      | MC-RU3.81SH04-0001 |

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat